

PT. Eternal Buana Chemical Industries JL. Raya Serang Km. 14 Cikupa, Tangerang, Indonesia

No. : EBCI/MSDS/3063 Issue date : Sept 01, 2004

Rev. no.

Rev. date Page no. : 1 of 3

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Trade Name : EBL - 3460

Chemical Name : Styrenated Acrylic Polymer Solution

Synonyms : None Molecular Formula : N/A

Chemical Family : Polymer Dispersion

II. INFORMATION ON INGREDIENT

Water : $70 \pm 1 \%$

Polymer Type : Styrenated Acrylic Free Monomer : 0.5 % max.

Others

III. HAZARDS IDENTIFICATION

Color : Clear to Amber Solution

Odor : Polymeric

Effect of over exposure : Contact with skin or eyes may cause minor temporary irritation.

Emergency and first aid procedures: Flush eyes with plenty amount of water for a minimum of 15 minutes. Wash contacted skin areas with soap and water. If irritation develops, consult a Physician. Soaked clothing should be change immediately.

IV. FIRST AID MEASURES

: Immediately rinse with running water for 15 minutes. Get medical attention, if First aid procedures - eyes irritation develops.

First aid procedures - skin : Wash affected areas with soap and water, gets medical attention if irritation develops.

First aid procedures – ingestion : Dilute with water if swallowed.

First aid procedures – inhalation : Remove to fresh air. If not breathing gives artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen and seek prompt medical attention.



PT. Eternal Buana Chemical Industries JL. Raya Serang Km. 14 Cikupa, Tangerang, Indonesia

No. : EBCI/MSDS/3063 Issue date : Sept 01, 2004

Rev. no. : Rev. date : Page no. : 2 of 3

V. FIRE FIGHTING MEASURES

Flash Point : (See physical data section)

Flammable Limits in Air, % by volume : Unknown
Lower : Undetermined Upper : Undetermined

Extinguishing Media : Use carbon dioxide or dry chemical on small fires. Use foam (alcohol,

polymer or ordinary) and water spray for large fires.

Special Fire Fighting Procedures : Self – contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

VI. ACCIDENTAL RELEASE MEASURES

Action to take spills: (Use appropriate safety equipment).

Use absorbent material to collect and contain for disposal. Contain large spills and pump into suitable tank. Wash the area with water and thoroughly rinse.

VII. STORAGE AND HANDLING

Store in well ventilated areas at temperature below 120 °F. Keep container tightly closed. Do not store or consume food, drink, or tobacco in area where they may become contaminated with this material.

VIII. PERSONAL PROTECTION

1. Local exhaust : None should be needed 2. Respiratory protection (type) : Canister for organic vapors

(i.e. type GMA from Mine Safety Appliance Co.)

Protective Clothing : clean, body-covering clothing. In addition, rubber gloves, boots and apron,

depending upon the exposure likely, or as required by your company).

Eye Protection : Safety goggles recommended.

IX. PHYSICAL PROPERTIES

Solubility in water : Soluble in all portion

Specific Gravity (gr/ml) : 1.04 - 1.09

Vapour Pressure, mm. Hg, : < 0.1

at 25°C

 ↓ Vapour Density (Air=1)

 : > 1

 ↓ Volatiles, %

 : < 1</td>

Appearance : Clear to Amber Solution



PT. Eternal Buana Chemical Industries JL. Raya Serang Km. 14 Cikupa, Tangerang, Indonesia

No. : EBCI/MSDS/3063 Issue date : Sept 01, 2004

Rev. no. :-Rev. date :-Page no. : 3 of 3

X. STABILITY AND REACTIVITY

🚣 Stab

Stability : Stable

Hazardous Decomposition Products : Thermal decomposition may produce carbon mono/ dioxides.

Hazardous polymerization : Will not occur

Condition to avoid : See above statement

XI. TOXICOLOGICAL INFORMATION

No applicable data for this section.

XII. ECOLOGICAL INFORMATION

No applicable data for this section.

XIII. DISPOSAL CONSIDERATION



Disposal Method: All local, state and federal regulation concerning health and pollution should be reviewed to determine approved disposal procedures.



Do not discharge into waterways or sewer system.

XIV. TRANSPORTATION INFORMATION

Not regulated by the department of transportation.

XV. REGULATORY INFORMATION

No additional information.

XVI. OTHER INFORMATION

Hazard Classification : Non - Hazardous
 Health Hazard : 0 - (Normal Material)
 Flammability : 0 - (Unflammable)
 Reactivity : 0 - (Stable)

This above data and information apply to the product as such and confirming to specifications given by PT. Eternal Buana Chemical Industries. While the information is believed to be correct, PT. Eternal shall in no event be responsible for any damages what so ever, directly or indirectly resulting from the publication or use of or reliance upon data contained here in. Users are advised of possible additional hazard when the product is used in applications for which it was not intended. This sheet only be used and reproduced for prevention and security purposes.