

### PT. ETERNAL BUANA CHEMICAL INDUSTRIES

BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920 PHONE: (62-21) 571 2998

FAX: (62-21) 571 2678

No. EBCI/MSDS/2039 Issue date January,01,1996

Rev. no. 01

October, 01, 2009 Rev. date

: 1 of 3 Page no.

## **MATERIAL SAFETY DATA SHEET**

### I. PRODUCT IDENTIFICATION

EBP 2524 V3 Product name

**Unsaturated Polyester Resin** Common chemical name

High reactivity and pre promoted of ortho type unsaturated polyester resin Synonyms

### **II. INFORMATION ON INGREDIENT**

Hazardous Ingredients **CAS Number** EC number 100-42-5 202-851-5 Styrene Monomer 10 - 40

### III. HAZARD IDENTIFICATION

Potential Health Effect:

Irritation, tearing, eye damage Eye contact: Irritation, symptoms of drunkenness Skin contact

Ingestion Irregular heartbeat, kidney damage, liver damage, cancer

Irritation, metallic taste, vomiting, headache, symptoms of drunkenness, liver Inhalation

damage, coma

### **IV. FIRST AID MEASURES**

Rinse with plenty of water immediately. Seek medical attention. Eye contact

Wash with plenty of soap and a large amount of water immediately. Take the Skin contact contaminated clothing off. Seek medical attention if irritation develops.

Do not induce vomiting because of risk of aspiration. Rinse mouth with water. Ingestion Seek medical attention.

Move to fresh air and take a rest. Apply artificial respiration if difficulty in Inhalation breathing. Seek medical attention after significant exposure.

## V. FIRE FIGHTING MEASURES

31.1 °C (tag closed cup). Flash Point 145,0° C (760,0 mmHg) Boiling point

490.0° C Ignition temperature

Use water spray to cool fire exposure surfaces and to protect personnel. Use Fire fighting

foam, dry chemical, or water spray to extinguish fire.

Carbon monoxide (CO). Hazardous product of combustion

Unusual fire & explosion hazard None known. 1,1 % Lower explosion limit 8.0 % Upper explosion limit

Wear protective clothing & use self-contained breathing apparatus. Protection of fire fighters



## PT. ETERNAL BUANA CHEMICAL INDUSTRIES

BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920 PHONE: (62-21) 571 2998

FAX: (62-21) 571 2678

No. EBCI/MSDS/2039 Issue date January,01,1996 Rev. no. 01

October, 01, 2009 Rev. date

Page no. 2 of 3

### VI. ACCIDENTAL RELEASE MEASURES

Use protective equipment. Personal precaution

Keep away from drains, ground water & soil. Environmental precaution

Collect as much as possible in a container for disposal. Cover the remainder Method for cleaning up with inert absorbent, sand or soil. Disposal according to local regulations.

### VII. STORAGE AND HANDLING

Handling Keep away from heat, sources of ignition, and no smoking.

Keep in a cool, dry and well-ventilated place. Storage

This product is stable under normal conditions of handling and storage.

### VIII. PERSONAL PROTECTION

Personal Protective Equipment

Skin & body

Use safety glasses with side shield. Eyes

Although this material doesn't irritate skin significantly. To minimize skin Hands contamination by following good industrial practice. Wearing protective gloves is recommended.

Although this material doesn't irritate skin significantly. To minimize skin

contamination by following good industrial practice. Wash contaminated skin thoroughly after handling. Avoid breathing vapour.

Use local exhaust ventilation or handle in a ventilated enclosure. For greater Respiratory system protection wear respiratory protective equipment is recommended.

# IX. PHYSICAL PROPERTIES

Liquid, Light red violet-pale Physical state & appearance

Viscosity at 25° C, Brookfield#3/60 250 - 350 cPs Styrene like Odor  $160 - 260^{\circ}C$ **Boiling point** Insoluble Water solubility 1.1 - 1.12 g/ml Specific Gravity (25°C)

### X. STABILITY & REACTIVITY

3-6 months Stability, in darkness at 25° C Condition to avoid Excessive heating. Material to avoid None known None known Hazardous Decomposition Product



## PT. ETERNAL BUANA CHEMICAL INDUSTRIES

BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920 PHONE: (62-21) 571 2998

FAX: (62-21) 571 2678

No. EBCI/MSDS/2039 Issue date : January,01,1996 Rev. no. 01

Rev. date October, 01, 2009

: 3 of 3 Page no.

## XI. TOXICOLOGICAL INFORMATION

PT. Eternal Buana Chemical Industries has not conducted toxicity studies on this material. No toxicological information is available

### XII. COMPONENT INFORMATION

Polycondensation product of carbodicylic acids or anhydrides with dihydroxy alcohols. The polymer is cotaining unsaturation and dissolved in styrene monomer as crosslinking agent.

## XIII. ECOLOGICAL INFORMATION

PT. Eternal Buana Chemical Industries has not conducted environmental toxicity or biodegradation studies on this material. No ecological information of this material is available.

## XIV. DISPOSAL CONSIDERATION

Disposal method

Controlled incineration or recycle.

### XV. TRANSPORT INFORMATION

International transportation regulations:

1866 UN number

Resin in solution (flammable liquids) Proper shipping name

Clasification of Hazardous Materials 3.3



## XVI. REGULATORY INFORMATION

Not available Local regulations

#### **XVII. OTHER INFORMATION**

This above data and information applies to the product as such and confirming to specifications given PT. Eternal Buana Chemical Industries. While the information is believed to be correct, PT. Eternal Buana Chemical Industries shall in no event be responsible for any damages what so ever, directly or indirectly resulting from the publication or use of or reliance upon data contained here in. Users are advised of possible additional hazard when the product is used in applications for which it was not intended. This sheet only be used and reproduced for prevention and security purposes.