






**PT. ETERNAL BUANA CHEMICAL INDUSTRIES**  
BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR  
JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920  
PHONE : (62-21) 571 2998  
FAX : (62-21) 571 2678


No. : EBCI/MSDS/2057  
Issue date : January,01,1996  
Rev. no. : 02  
Rev. date : October, 01, 2009  
Page no. : 1 of 3

## MATERIAL SAFETY DATA SHEET

### I. PRODUCT IDENTIFICATION





 Product name : PT 2318  
 Common chemical name : Accelerator for unsaturated polyester Resin  
 Synonyms : Cobalt based metallic solution for using as accelerator especially for poly putty

### II. INFORMATION ON INGREDIENT





Hazardous Ingredients	%	CAS Number	EC number
 Styrene Monomer	10 - 40	100-42-5	202-851-5

### III. HAZARD IDENTIFICATION










Potential Health Effect:

 Eye contact : Irritation, tearing, eye damage  
 Skin contact : Irritation, symptoms of drunkenness  
 Ingestion : Irregular heartbeat, kidney damage, liver damage, cancer  
 Inhalation : Irritation, metallic taste, vomiting, headache, symptoms of drunkenness, liver damage, coma

### IV. FIRST AID MEASURES

 Eye contact : Rinse with plenty of water immediately. Seek medical attention.  
 Skin contact : Wash with plenty of soap and a large amount of water immediately. Take the contaminated clothing off. Seek medical attention if irritation develops.  
 Ingestion : Do not induce vomiting because of risk of aspiration. Rinse mouth with water. Seek medical attention.  
 Inhalation : Move to fresh air and take a rest. Apply artificial respiration if difficulty in breathing. Seek medical attention after significant exposure.

### V. FIRE FIGHTING MEASURES




 Flash Point : 31.1 °C (tag closed cup).  
 Boiling point : 145,0° C (760,0 mmHg)  
 Ignition temperature : 490,0° C  
 Fire fighting : Use water spray to cool fire exposure surfaces and to protect personnel. Use foam, dry chemical, or water spray to extinguish fire.  
 Hazardous product of combustion : Carbon monoxide (CO).  
 Unusual fire & explosion hazard : None known.  
 Lower explosion limit : 1,1 %  
 Upper explosion limit : 8,0 %  
 Protection of fire fighters : Wear protective clothing & use self-contained breathing apparatus.





**PT. ETERNAL BUANA CHEMICAL INDUSTRIES**  
BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR  
JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920  
PHONE : (62-21) 571 2998  
FAX : (62-21) 571 2678

No. : EBCI/MSDS/2057  
Issue date : January,01,1996  
Rev. no. : 02  
Rev. date : October, 01, 2009  
Page no. : 2 of 3

## VI. ACCIDENTAL RELEASE MEASURES

-  Personal precaution : Use protective equipment.
-  Environmental precaution : Keep away from drains, ground water & soil.
-  Method for cleaning up : Collect as much as possible in a container for disposal. Cover the remainder with inert absorbent, sand or soil. Disposal according to local regulations.





## VII. STORAGE AND HANDLING

-  Handling : Keep away from heat, sources of ignition, and no smoking.
-  Storage : Keep in a cool, dry and well-ventilated place.







This product is stable under normal conditions of handling and storage.

## VIII. PERSONAL PROTECTION





### Personal Protective Equipment

-  Eyes : Use safety glasses with side shield.
-  Hands : Although this material doesn't irritate skin significantly. To minimize skin contamination by following good industrial practice. Wearing protective gloves is recommended.
-  Skin & body : Although this material doesn't irritate skin significantly. To minimize skin contamination by following good industrial practice. Wash contaminated skin thoroughly after handling. Avoid breathing vapour.
-  Respiratory system : Use local exhaust ventilation or handle in a ventilated enclosure. For greater protection wear respiratory protective equipment is recommended.

## IX. PHYSICAL PROPERTIES

-  Physical state & appearance : Blue violet & clean liquid
-  Metal content,% : 47 - 50
-  Odor : Styrene like
-  Boiling point : 160 – 260° C
-  Water solubility : Insoluble
-  Specific Gravity (25°C) : 0,83 – 0,87 g/ml

## X. STABILITY & REACTIVITY

-  Stability, in darkness at 25° C : 3 – 6 months
-  Condition to avoid : Excessive heating.
-  Material to avoid : None known
-  Hazardous Decomposition Product : None known



**PT. ETERNAL BUANA CHEMICAL INDUSTRIES**  
BARCLAYS HOUSE, 7<sup>TH</sup> FLOOR  
JL. JENDERAL SUDIRMAN KAV 22-23 JAKARTA 12920  
PHONE : (62-21) 571 2998  
FAX : (62-21) 571 2678

No. : EBCI/MSDS/2057  
Issue date : January,01,1996  
Rev. no. : 02  
Rev. date : October, 01, 2009  
Page no. : 3 of 3


## XI. TOXICOLOGICAL INFORMATION

PT. Eternal Buana Chemical Industries has not conducted toxicity studies on this material. No toxicological information is available

## XII. ECOLOGICAL INFORMATION




PT. Eternal Buana Chemical Industries has not conducted environmental toxicity or biodegradation studies on this material. No ecological information of this material is available.

## XIII. DISPOSAL CONSIDERATION

 Disposal method : Controlled incineration or recycle.


## XIV. TRANSPORT INFORMATION

International transportation regulations :

 UN number : 1866  
 Proper shipping name : Resin in solution (flammable liquids)  
 Classification of Hazardous Materials : 3.3



## XV. REGULATORY INFORMATION

 Local regulations : Not available

## XVSI. OTHER INFORMATION

This above data and information applies to the product as such and confirming to specifications given by PT. Eternal Buana Chemical Industries. While the information is believed to be correct, PT. Eternal Buana Chemical Industries shall in no event be responsible for any damages what so ever, directly or indirectly resulting from the publication or use of or reliance upon data contained here in. Users are advised of possible additional hazard when the product is used in applications for which it was not intended. This sheet only be used and reproduced for prevention and security purposes.