

**TECHNICAL DATA SHEET****ACRYNAL 7303 - 60****I. DESCRIPTION**

ACRYNAL 7303 - 60 is a hydroxyl functional acrylic copolymer designed to cross-link at room temperature with polyisocyanate adducts. This resin has been primarily developed to produce two-pack system with the following outstanding features.

**II. PERFORMANCE**

- Excellent chemical and stain resistance.
- Excellent adhesion.
- Excellent durability.
- Excellent hardness.
- Excellent flexibility.

**III. SUGGESTED USES**

- Automotive & general metal coatings.
- Plastic coatings.
- Wood coatings.

**IV. SPECIFICATION**

- Non-Volatile (150 °C, 15 mins) : 60 ± 1 %
- Viscosity (25 °C, Gardner-Holdt) : Z<sub>3</sub> - Z<sub>5</sub>
- Acid value (mg KOH /g solid) : 8 - 11
- Color (Gardner-Holdt) : maximum 1
- Appearance : Clear and Clean
- Specific Gravity (25 °C) : ca. 1.028
- OH Value (mg KOH/g solid) : 75 ± 5

**V. STANDARD PACKING**

210 kgs in metal drums.

**VI. STORAGE AND HANDLING**

- Store in proper warehouse.
- Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.