



TECHNICAL DATA SHEET

EBA 1366 - 60 LV

I. DESCRIPTION

EBA 1366 - 60 LV is a medium oil alkyd based on soya bean oil with superiority in drying time and yellowing resistance.

II. PERFORMANCE

- Fast Dry.
- Excellent whiteness.
- Excellent hardness.
- Excellent gloss and gloss retention.
- Good yellowing resistance.

III. SUGGESTED USES

- High quality industrial and white decorative enamel for wood and steel.

IV. SPECIFICATION

- Non-Volatile (150 °C, 15 mins) : 60 ± 1 %
- Viscosity (25 °C, Gardner-Holdt) : Z1 - Z3 (50 % in white spirit)
- Acid Value (mg KOH/g solid) : maximum 15
- Color (Gardner-Holdt) : maximum 5 (50 % in white spirit)
- Appearance : clean & clear
- Specific Gravity (25 °C) : ca. 0.955

V. STANDARD PACKING

200 kgs in metal drums.

VI. STORAGE AND HANDLING

- Store in proper warehouse.
- Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.