



TECHNICAL DATA SHEET

EBA 1463 - 70 HV

I. DESCRIPTION

EBA 1463 - 70 HV is a short oil alkyd resin based on soya bean oil with high viscosity. It can be used for NC lacquer and acid curing.

II. PERFORMANCE

- High viscosity.
- Fast dry.
- Good hardness.
- Good adhesion.
- Good gloss and gloss retention.

III. SUGGESTED USES

- Amino - Alkyd acid curing.
- NC lacquer.

IV. SPECIFICATION

- | | |
|------------------------------------|------------------------------|
| • Non-Volatile (150 °C, 15 mins) | : 70 ± 1 % |
| • Viscosity (25 °C, Gardner-Holdt) | : Z5 - Z7 (60 % in xylene) |
| • Acid Value (mg KOH/g solid) | : maximum 10 |
| • Color (Gardner-Holdt) | : maximum 3 (60 % in xylene) |
| • Appearance | : clean & clear |
| • Specific Gravity (25 °C) | : ca. 1.038 |
| • OH Value (mg KOH/g solid) | : ca. 160 |

V. STANDARD PACKING

210 kgs in metal drums.

VI. STORAGE AND HANDLING

- Store in proper warehouse.
- Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.