

TECHNICAL DATA SHEET

EBA 1486 - 70

I. DES EBAIPTION

EBA 1486 - 70 is a high viscosity short oil alkyd resin based on mixture of vegatable oils. It can be used for NC lacquer, acid curing, and baking finishes.

II. PERFORMANCE

- Fast dry.
- Good hardness.
- Good adhesion.
- Good gloss and gloss retention.
- Good stability.

III. SUGGESTED USES

- Amino Alkyd acid curing.
- NC lacquer.
- Baking enamel.

IV. SPECIFICATION

• Non-Volatile (150 °C, 15 mins) : 68.5 - 71%

• Viscosity (25 °C, Gardner-Holdt) : Z₆ - Z₇ (60 % in xylene)

• Acid Value (mg KOH/g solid) : maximum 10

• Color (Gardner-Holdt) : maximum 4 (60 % in xylene)

Appearance : clean & clear
Specific gravity (25 °C) : ca. 1.0703

V. STANDARD PACKING

210 kgs in metal drums.

VI. STORAGE AND HANDLING

- Store in proper warehouse.
- Keep container closed when not in use.

The information contained herein is correct to the best of our knowledge. The recommendations or suggestions contained in this bulletin are made without guarantee or representation as to results. We suggest that you evaluate these recommendations and suggestions in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, regligence or otherwise is limited to the purchase price of the material.